AX61132TM

1U Rackmount Chassis for ATX Motherboard

Features

- Supports 12" x 9.6" standard ATX MB (IMB206/IMB207/IMB208/IMB211)
- Internal two SATA HDD drive bays
- Supports one PCI riser card
- Supports ATX 270W power supply









▲ Rear view

Specifications

Standard Color	Black	
Construction	Heavy-duty steel	
Drive Capacity	nternal 2 x SATA HDD drive bay	
Cooling	2 x 4 cm ball bearing fans (15.3 CFM/each)	
Front Panel Indicators	1 x power on/off, 1 x HDD	
Front Panel Controls	1 x power on/off	
Front Panel Connectors	N/A	
Pre-punched Panel	N/A	
System Board	IMB206/IMB207/IMB208/IMB211	

Expansion Interface	1 x PCI slot (32 bits/33 MHz)
Operating Temperature	0°C ~ +40°C (+32°F ~ +104°F)
Dimensions	482 mm (19") (W) x 430 mm (16.9") (D) x 44 mm (1.73") (H)
Weight (net/gross)	9.8 kg (21.6 lb)/10.5 kg (23.15 lb)

Power Supply Specifications

Items	Watt	Specifications			
		Input	Output	MTBF	
PS270-1U	ATX 270W (PFC)	AC 90~264V (Auto)	+5V @ 18A +12V 1 @ 16A +12V 2 @ 10A +3.3V @ 16A -12V @ 0.8A +5VSB @ 2.5A	100,000 hours	

Recommended MB Selections

IMB206 with LGA1156 heatsink (manufacture option) IMB207 with LGA1156 heatsink (manufacture option) IMB208 with LGA1156 heatsink (manufacture option) IMB211 with LGA1156 heatsink (manufacture option)

Optional Items

E296200100	AX96200 1-slot 32-bit PCI riser card
50761133100E	LGA1156 1U passive CPU cooler

Ordering Information

AND 132 IIVI/N270 VVIIII AIN 270 V POVICI SU	AX61132TM/X270	With ATX 270W power su	upply
--	----------------	------------------------	-------

^{*}Specifications and certifications are based on options and may vary.

Dimensions

