

# AX61133TM

1U Dual Hot swapping SATA HDD Tray Rackmount classis for ATX Motherboard

## Features

- Supports 12" x 9.6" standard ATX Motherboard (IMB206/IMB207/IMB208)
- Supports two 3.5" SATA HDD (hot-swappable tray)
- Supports one PCI or PCIe riser card
- Supports ATX 270W power supply



Supports 2 x 3.5" hot-swappable SATA HDD tray  
Easy-to-maintain tray design



▲ Front view



▲ Rear view



## Specifications

Standard Color	Black
Construction	Heavy-duty steel
Drive Capacity	Exposed 2 x SATA HDD drive bay (hot swappable tray)
Cooling	2 x 4 cm ball bearing fans (15.3 CFM/each)
Front Panel Indicators	1 x power on/off, 1 x HDD
Front Panel Controls	1 x power on/off
Front Panel Connectors	N/A
Pre-punched Panel	N/A
System Board	IMB206/IMB207/IMB208

Expansion Interface	1 x PCI slot (32 bits/33 MHz) or 1 x PCIe slot
Operating Temperature	0°C ~ +40°C (+32°F ~ +104°F)
Dimensions	473.5 mm (19") (W) x 440 mm (17.32") (D) x 44 mm (1.73") (H)
Weight (net/gross)	9.8 kg (21.6 lb)/10.8 kg (23.8 lb)

## Power Supply Specifications

Items	Watt	Input	Specifications	MTBF
			Output	
PS270-1U	ATX 270W (PFC)	AC 90-264V (Auto)	+5V @ 18A	100,000 hours
			+12V 1 @ 16A	
			+12V 2 @ 10A	
			+3.3V @ 16A	
			-12V @ 0.8A	
+5VSB @ 2.5A				

## Ordering Information

AX61133TM/X270	With ATX270W Power supply, PCI version
AX61133TM/X270	With ATX270W Power supply, PCIe version

\*Specifications and certifications are based on options and may vary.

## Recommended MB Selections

IMB206 with LGA1156 heatsink (manufacture option)  
 IMB207 with LGA1156 heatsink (manufacture option)  
 IMB208 with LGA1156 heatsink (manufacture option)

## Optional Items

E296200100	AX96200 1-slot 32-bit PCI riser card
84306113300E	PCIe x16 riser card L: 3250 mm
50761133100E	LGA1156 1U passive CPU cooler

## Dimensions

