

OPS885

Intelligent Pluggable System Specification (IPSS) Digital Signage Player with 4th Gen Intel® Core™ i5, Intel® QM87, AMT 9.0 and TPM 1.2

Features

- Open Pluggable Specification (OPS) compliance
- 4th gen Intel® Core™ i5-4400E processor onboard (Haswell)
- Intel® QM87 chipset
- DDR3L-1600 SO-DIMM, up to 8GB
- 2 USB 3.0 ports and 2 PCIe Mini Card slots
- HDMI for 2nd display
- Supports 4K resolution
- Supports TPM 1.2
- Intel® AMT (Active Management Technology) 9.0
- Intel® RCM (Retail Client Manager)



- | | | |
|-----------------|---------------------|-----------------------------|
| 1. USB 3.0 x 2 | 5. Reset | 9. RS-232 |
| 2. Ethernet | 6. HDD indicator | 10. USB 2.0 |
| 3. HDMI | 7. Audio (Line-out) | 11. WiFi antenna (optional) |
| 4. Power switch | 8. Audio (Mic.-in) | 12. JAE TX-25 |



Specifications

| | | |
|--|--|---|
| Main System | CPU | Intel® Core™ i5-4400E processor onboard (Haswell) |
| | Chipset | Intel® QM87 |
| | System Memory | 1 x 204 pin DDR3L-1600 SO-DIMM, up to 8GB |
| | Storage | 1 x mSATA |
| | BIOS | AMI UEFI BIOS with OA 3.0 built |
| | Watchdog Timer | 255 levels, 1 – 255 sec. |
| I/O | 2 x USB 3.0 | |
| | 1 x USB 2.0 | |
| | 1 x 10/100/1000 Mbps Ethernet (Intel® i217LM) | |
| | 1 x HDMI | |
| | 1 x RS-232 (COM 2) | |
| | 1 x Power on/off button | |
| | 1 x Reset button | |
| | 1 x Audio (Line-out) | |
| | 1 x Audio (Mic-in) | |
| | 1 x DisplayPort (via OPS JAE interconnector) (Pure DP) | |
| | 2 x USB 2.0 (via OPS JAE interconnector) | |
| | 1 x USB 3.0 (via OPS JAE interconnector) | |
| | 1 x HDMI/DVI (via OPS JAE interconnector) | |
| 1 x Audio (Line-out, via OPS JAE interconnector) | | |
| 1 x UART (TX/RX, via OPS JAE interconnector) (COM 1) | | |
| Indicator | 1 x LED for system power on | |
| WiFi | 802.11 b/g/n (optional) | |
| Expansion Slot | 2 x full-size PCIe Mini Card slot 1 x SIM slot | |
| Dimensions | 200 mm (7.87") (W) x 119 mm (4.68") x 30 mm (1.18") | |
| Packing Dimensions | 270 mm (10.63") (W) x 197 mm (7.76") x 70 mm (2.76") | |
| Weight (net/gross) | 1 kg (2.21lb)/1.5kg (3.3 lb) | |
| Environmental | 0° ~ +45°C (+32°F ~ +113°F) (with airflow 1.2m/s) | |

Packing

- 1 x Driver CD
- 1 x Thermal grease
- 2 x M2 x 3 screw
- 2 x M3 x 4 screw
- 2 x M4 x 10 screw
- 2 x Thermal pad

Optional OS Installation

Windows® 7, Windows® 8.1

Ordering Information

Standard

| | |
|------------------|---|
| OPS885 | IPSS/OPS digital signage player with Intel® Core™ i5-4400E (3M Cache, up to 3.30 GHz) processor onboard |
| (P/N:E22M885100) | |

Optional

| | |
|---------|--|
| AX93157 | OPS docking board |
| AX93167 | OPS docking board with 4K resolution support |

* Specifications and certifications may vary contingent on options.

Dimensions

