

# NA361

Desktop Network Appliance Platform with Intel® Atom® Processor C2358 and 6 LAN

## Features

- Intel® Atom® processor C2358 (Rangeley)
- Two DDR3-1600 U-DIMM for up to 16GB of memory
- Six 10/100/1000 Mbps Ethernet ports (Intel® i354 & Intel® i210)
- Wi-Fi/3G/LTE through PCI Express Mini Card for optional
- Supports Intel® QuickAssist Technology
- Supports Intel® Data Plane Development Kit (Intel® DPDK)
- Suitable for VPN, network bandwidth controller, firewall and UTM applications




## Specifications

| System              |   |
|---------------------|---|
| CPU                 | Intel® Atom® processor C2358 (2-core) (Rangeley)  |
| Chipset             | SoC integrated  |
| Memory              | 2 x DDR3-1600 U-DIMM, up to 16GB non-buffer non-ECC/ECC memory                                  |
| BIOS                | AMI SPI Flash BIOS  |
| Storage             | 1 x 2.5" SATA HDD<br>1 x CompactFlash™ type-II<br>1 x mSATA (optional)<br>1 x CFast™ (optional) |
| Network Interface   | 6 x 10/100/1000 Mbps Ethernet (Intel® i354 & Intel® i210)<br>4 x RJ-45 + 2 x SFP (optional)     |
| I/O                 | 1 x RS-232 (RJ-type)<br>2 x USB 2.0<br>6 x RJ-45  |
| Other Features      | LAN Bypass function through latch relay (two pairs) for optional                                |
| Expansion Interface | 1 x PCI Express Mini Card slot with USB interface   |
| Watchdog Timer      | 255 stepping for system reset<br>8 stepping for LAN Bypass                                      |
| Power Supply        | 1 x 12V, 5A power adapter   |
| OS Compatibility    | Yocto, Linux  |

## Mechanical/ Environmental

|                       |  |
|-----------------------|--|
| Form Factor           | 1U desktop   |
| LED                   | Power, HDD, GPIO programmable, LAN Bypass, Link/Act with transfer rate |
| Operating Temperature | 0°C to +40°C (+32°F to +104°F)   |
| Humidity              | 10% - 95% RH, non-condensing   |
| Chassis Material      | Steel  |
| Dimensions            | 44 mm (1.73") (H) x 231 mm (9.09") (W) x 197 mm (7.76")                |
| Weight (net/gross)    | 2.35 kg (5.18 lb)/2.61 kg (5.75 lb)                                    |
| Certifications        | FCC class B/CE class B   |



## Ordering Information

| Standard                                    |  |
|---|--|
| NA361-D6GI-2358-US (P/N: E26E361100)        | 1U compact network appliance with Intel® Atom® processor C2358 and 6 GbE LAN             |
| NA361-D6GI-2358-US w/ LBP (P/N: E26E361101) | 1U compact network appliance with Intel® Atom® processor C2358, 6 GbE LAN and LAN Bypass |

| Optional     |   |
|--------------|---|
| 5916E552000E | DB9F-RJ-45 1.8M console cable for Cisco |

\* Specifications and certifications may vary based on different requirements.

## Packing List

- 1 x DC power adapter 12V/5A
- 1 x Power cord
- 1 x SATA cable

## Dimensions

